


50 Hz seçim aralığı: Q= 68 m ³ /sa - 112 m ³ /sa Standart Klepe Çıkışı : 5" İçten Pasolu 11 Diş (NPT : Özel istek) Fan tipi: Semiaksiyel Dönüş : Saat Yönü Ters Bağlantı : NEMA Standardına uygun Mil Çapı : 25 mm	
Minimum sıvı seviyesi: Emiş süzgecinin altından itibaren 1200 mm. Maksimum pompa dış çapı (Kablo muhafazası ile birlikte): 182 mm	
Pompalanan Sıvı: Kimyasal ve mekanik aşındırıcı olmayan akışkan. İzin verilen maksimum kum miktarı = 50 g/m ³ İzin verilen katı parçacık ölçüsü: Max 2mm	
İmalat ve güvenlik standartları: TS 11146:1993 TS EN ISO 12100-1:2007	Tarih 01 / 2013 REV. 0
TS EN 809:2000 98/37/EC TS EN ISO 12100-2:2006	

Operating range at 50 Hz: Q= 68 m ³ /h - 112 m ³ /h Standard Outlet : 5" Inside Threaded 11 TPI (NPT : Optional) Impeller type: Mixed flow Rotation : CCW Connection : According to NEMA Standard Shaft Diameter : 25 mm	
Minimum liquid level (NPSH) : 1200 mm from bottom of suction grid Maximum pump (Wet end) diameter - (Including cable guard): 182 mm	
Liquid being pumped: Chemically and mechanically non aggressive. Maximum allowable solid quantity = 50 g/m ³ Solid dimension: Max 2mm	
Construction and safety standards: TS 11146:1993 TS EN ISO 12100-1:2007	Date 01 / 2013 REV. 0
TS EN 809:2000 98/37/EC TS EN ISO 12100-2:2006	



POMPA TİPİ PUMP TYPE	MOTOR MOTEUR			ÖLÇÜLER / DIMENSIONS (mm)										AĞIRLIK / WEIGHT (kg)								
	6" HP	8" HP	kW	8"-6"		8"-8"		6"		8"		8"-6"		8"-8"		ø D	MOTOR		POMPA PUMP		TOPLAM TOTAL	
				L	L	E	E	B	B	ø = C	ø = C	ø PUMP	ø PUMP	6"	8"		8"-6"	8"-8"	8"-6"	8"-8"		
SS 896/01	5,5	-	4	1200	-	630	-	570	-	145	-	174	-	5"	46	-	22	-	68	-		
SS 896/02	10	-	7,5	1348	-	650	-	698	-	145	-	174	-	5"	48	-	25	-	73	-		
SS 896/03	15	-	11	1556	-	730	-	826	-	145	-	174	-	5"	56	-	29	-	85	-		
SS 896/04	20	-	15	1784	-	830	-	954	-	145	-	174	-	5"	60	-	32	-	92	-		
SS 896/05	25	-	18,5	1962	-	880	-	1082	-	145	-	174	-	5"	72	-	35	-	107	-		
SS 896/06	30	30	22	2190	2151	980	930	1210	1221	145	195	174	182	5"	82	121	38	40	120	161		
SS 896/07	35	35	26	2368	2389	1030	1040	1338	1349	145	195	174	182	5"	88	140	41	42	129	182		
SS 896/08	40	40	30	2576	2517	1110	1040	1466	1477	145	195	174	182	5"	98	140	44	45	142	185		
SS 896/09	50	50	37	2784	2675	1190	1070	1594	1605	145	195	174	182	5"	106	146	47	47	153	193		
SS 896/10	50	50	37	2912	2803	1190	1070	1722	1733	145	195	174	182	5"	106	146	50	50	156	196		
SS 896/11	60	60	45	3120	2991	1270	1130	1850	1861	145	195	174	182	5"	116	158	53	53	169	211		
SS 896/12	60	60	45	3248	3119	1270	1130	1978	1989	145	195	174	182	5"	116	158	56	55	172	213		
SS 896/13	-	70	52	-	3327	-	1210	-	2117	-	195	-	182	5"	-	177	-	58	-	235		
SS 896/14	-	70	52	-	3455	-	1210	-	2245	-	195	-	182	5"	-	177	-	60	-	237		
SS 896/15	-	75	55	-	3623	-	1250	-	2373	-	195	-	182	5"	-	184	-	63	-	247		
SS 896/16	-	80	59	-	3781	-	1280	-	2501	-	195	-	182	5"	-	190	-	65	-	255		
SS 896/17	-	90	66	-	3994	-	1365	-	2629	-	195	-	182	5"	-	204	-	68	-	272		
SS 896/18	-	90	66	-	4122	-	1365	-	2757	-	195	-	182	5"	-	204	-	70	-	274		
SS 896/19	-	100	75	-	4315	-	1430	-	2885	-	195	-	182	5"	-	218	-	73	-	291		
SS 896/20	-	100	75	-	4443	-	1430	-	3013	-	195	-	182	5"	-	218	-	75	-	293		
SS 896/21	-	110	81	-	4641	-	1500	-	3141	-	195	-	182	5"	-	230	-	78	-	308		
SS 896/22	-	110	81	-	4769	-	1500	-	3269	-	195	-	182	5"	-	230	-	81	-	311		
SS 896/23	-	125	92	-	5017	-	1620	-	3397	-	195	-	182	5"	-	252	-	83	-	335		

POMPA TİPİ PUMP TYPE	MOTOR MOTEUR			m ³ /h															
	6" HP	8" HP	kW	Total Dynamic Head (TDH)															
				l / sec	0,00	18,89	20,00	21,11	22,22	23,33	24,44	25,56	26,67	27,78	28,89	30,00	31,11		
SS 896/01	5,5	-	4	16	14	13	13	13	13	12	12	11	10	10	9	9			
SS 896/02	10	-	7,5	33	28	27	26	26	25	24	23	22	21	19	18	17			
SS 896/03	15	-	11	50	41	40	39	38	38	36	35	33	31	29	27	26			
SS 896/04	20	-	15	67	55	54	52	51	50	48	46	44	42	39	36	34			
SS 896/05	25	-	18,5	84	69	67	66	64	63	60	58	55	52	49	45	43			
SS 896/06	30	30	22	100	83	80	79	77	75	72	69	66	62	58	54	51			
SS 896/07	35	35	26	117	97	94	92	90	88	84	81	77	73	68	63	60			
SS 896/08	40	40	30	134	110	107	105	102	100	96	92	88	83	78	72	68			
SS 896/09	50	50	37	151	124	121	118	115	113	108	104	99	94	87	81	77			
SS 896/10	50	50	37	160	138	134	131	128	125	120	115	110	104	97	90	85			
SS 896/11	60	60	45	184	152	147	144	141	138	132	127	121	114	107	99	94			
SS 896/12	60	60	45	201	166	161	157	154	150	144	138	132	125	116	108	102			
SS 896/13	-	70	52	218	179	174	170	166	163	156	150	143	135	126	117	111			
SS 896/14	-	70	52	225	193	188	183	179	175	168	161	154	146	136	126	119			
SS 896/15	-	75	55	242	207	201	197	192	188	180	173	165	156	146	135	128			
SS 896/16	-	80	59	257	221	214	210	205	200	192	184	176	166	155	144	136			
SS 896/17	-	90	66	274	235	228	223	218	213	204	196	187	177	165	153	145			
SS 896/18	-	90	66	302	248	241	236	230	225	216	207	198	187	175	162	153			
SS 896/19	-	100	75	319	262	255	249	243	238	228	219	209	198	184	171	162			
SS 896/20	-	100	75	336	276	268	262	256	250	240	230	220	208	194	180	170			
SS 896/21	-	110	81	352	290	281	275	269	263	252	242	231	218	204	189	179			
SS 896/22	-	110	81	369	304	295	288	282	275	264	253	242	229	213	198	187			
SS 896/23	-	125	92	386	317	308	301	294	288	276	265	253	239	223	207	196			

Katalogtaki hidrolik karakteristikler çekvalf kayıplarını içermez. Hydraulic characteristics of catalog don't include the loss of check-valve

Performans eğrileri Performance Curves 1 – 23

